TriPowerTM Pad

www.gymfloorresource.com • 855-310-6983





TriPower[™] Pad

TriPowerTM Pad offers superior shock absorption and vibration dampening. The unique blend of EPDM ensures stability and longevity required by high performance floors.



- 1. Structural Webs Cross-Linked
 - a. Greater load carrying ability
 - b. Vibration attenuation
 - c. Increased uniformity and consistent response
- 2. Stage II Heavy-Duty Load Distribution
- 3. 3-point Surface Contact Shock Pads Athletic Resilience

Composition

EPDM Rubber / Recyclable

Hardness Shore A

Black, 1/2" (12mm), 50D

ASTM Durometer

Red, 3/4" (19mm), 70D Black, 3/4" (19mm), 60D

Blue, 3/4" (19mm), 50D

Triangular Footprint 3 Point Primary Surface Contact

1 Point Secondary Load

Contact

ASTM D412 Tensile PSI 1810

ASTM D412 Elongation 648

Loading

Excellent

Performance Information












Aacer systems meet and exceed all 3rd party industry testing standards.


- ASTM 2137 low temperature brittleness
 - · 3 min @ -40 pass
- ASTM D395 compression set
 - · 22 hours @ 70c set % -20

U.S. Patent #

#5,988,915

DETAIL DRAWINGS





AACER PAD OPTIONS



TriPower™ Black 1/2" (12mm) 50D



TriPower™ Red 3/4" (19mm) 70D



TriPower™ Black 3/4" (19mm) 60D



TriPower™ Blue 3/4" (19mm) 50D



ECO 1/4" (6mm), 1/2" (12mm), 3/4" (19mm)



AacerCush 3/8" (10mm)



Open Cell Foam 1/2" (12mm), 3/4" (19mm)



Performance Foam 1/4" (6mm), 1/2" (12mm), 3/4" (19mm)



It is the policy of Infinity Wood Floors to continuously improve its line of products. Therefore, Infinity Wood Floors reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.























